



## USA WORKING EQUITATION



### Obstacle Specifications

No. of obstacles required	<b>L1–L3:</b> 10. <b>L4 &amp; L5:</b> 13. <b>L6 &amp; L7:</b> 15.
Distance btw consecutive obstacles and entry/exit	10 m (30 ft) min. (line of travel)
Distance from public	5 m (15 ft) min.
Entrance/exit markers	1.5 m (5 ft) min; 3 m (10 ft) max.
1. Bridge	Entry/exit markers are required.
2. Figure 8	Distance between drums: 3-m (10-ft) on center.
3. Pen	Outer pen: 6 m (20 ft) in dia. Inner pen 3 m (10 ft) in dia. Entrance: 1.5 to 2.5 m (5- to 8-ft). Corridor: 1.5 m (5-ft).
4. Jug	Table: 1.2 m (4 ft). Jug must be in same position for all competitors. Must be accessible from either side. Entry/exit markers are required.
5. Remove Pole	Pole: 2.5 to 3.5 m (8 to 11.5 ft). Must be accessible from either side.
6. Spear Ring	Ring: 15 cm (6 in.) in dia. (approx.). Must be accessible from either side.
7. Replace Pole	Must be accessible from either side.
8. Switch Cup	Bending poles: 2 m (6.5 ft) high (approx.). Distance: 1.2 m (4 ft) apart. Cup: must be set on same pole for all riders <i>unless WAWE rules are used</i> .
9. Bell Corridor	Rails: 30 cm (12 in.) high; 3.7 m (12 ft.) long; 1.5 m (5 ft.) apart. Bell: 2 m (6.5 ft) high; positioned in center of corridor.
10. Reinback “L”	Rails: 30 cm (12 in.) high (min); 3.7 m (12 ft) long. “L” in either direction. Corridor width: 1.5 m (5 ft).
11. Rounding Posts	Corridor width: 1.5 m (5 ft). Distance btw posts: 2.5 m (8 ft) min; 3 m (10 ft) max.
12. Single Slalom	Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Entry/exit markers are recommended.
13. Double Slalom	Posts: 2 m (6.5 ft) high. Distance btw posts: 6 m (20 ft). Corridor width: 6 m (20 ft). Entry/exit markers are recommended.
14. Gate	Height: 1.3 m (4 ft 3 in.) min. Width: 2 m (6.5 ft) min.
15. Jump	Width: 3 m (10 ft) min. <b>L1:</b> ground rail between standards, jump cups removed. Two ground rails may be used, 1 to 1.2 m (3.5 to 4 ft) apart. <b>L2/L3:</b> Crossed rails 0.5 m (22 in.) at standard; 0.4 m (15 in.) at center. <b>L4–L7:</b> 0.5 m (22 in.) high. Must have a ground pole.
16. Sidepass Rail	Rail: 10 cm (4 in.) dia.; 3.7 m (12 ft) long; 5-10 cm (2-4 in) above ground. Two rails in line or parallel rails: 3 m (10 ft) apart Zigzag configuration: angles set at 90 degrees. Entry/exit markers are required.
17. Water	Minimum 1.5 m (5 ft) long; 2.4 m (8 ft) wide; 10 cm (4 in.) deep; maximum depth 20 cm (8 in.)
18. Bank	30-60 cm (1-2 ft) above ground level. Plateau 2 m (6.5 ft) long.
19. Drums	<b>L1–L5:</b> 4 m (13 ft); <b>L6 &amp; L7:</b> 3 m (10 ft)
20. Move Sack	Table: 1.2 m (4 ft). Sack 4.5 kg (10 lb) max.
21. Drag Item	Table: 1.2 m (4 ft). Lariat: 6 m (20 ft).
22. Varied Footing	1.2 x 2.4 m (4 x 8 ft) minimum.
23. Herding Cattle	Panel height: 1.5 - 2.1 m (5 - 7 ft). Enclosure: 6 x 6 m (20 x 20 ft)